



ASPIKLER N

ASPIKLER N

BUILDINGS & CONSTRUCTION

Applications

For sewer suction.
Also for suction or delivery of abrasive materials on stationary systems and for cassette applications on sewer cleaning vehicles.

Advantages

- High resistance to abrasive environment and abrasive transportation media.
- Suitable both for suction and pressure.

Technical description

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile cords with embedded steel helix.

Cover: SBR/NR, black, fabric impression.

Temperature range: -30 °C to +80 °C.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock or min. order m
100 ±1.0	8.0	116,5 ±1.5	6.0	15	0.9	450	4.3	20	0095016	•
								40	0096724	200
125 ±1.2	9.5	144 ±1.5	6.0	15	0.9	550	6.3	20	0094152	•
								40	5009671	200
150 ±1.2	10.0	170 ±1.5	6.0	15	0.9	650	7.77	20	5008847	•

☐Upon availability.

* Tolerance on length: ± 1 % (ISO 1307 Standard)

Branding

ASPIKLER N

Made in France



TRELLEBORG