



# KLERIX

## KLERIX BUILDINGS & CONSTRUCTION

### Applications

For use in sewer cleaning water pressure applications.  
Suitable for replacing hydraulic hoses used in this application.

### Advantages

- Abrasion and weather resistant cover compound.
- Smooth cover, low friction.
- Long lengths.

### Technical description

**Inner tube:** SBR, black, smooth.

**Reinforcement:** steel, braided.

**Cover:** SBR/NR, black, smooth.

**Temperature range:** -30 °C to +80 °C.

### Couplings/Fittings

Hydraulic coupling.

### Complementary information

Delivered without couplings.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock or min. order m
13 ±0.8	5.0	23 ±0.8	200.0	500	70	0.45	40	0071107	•
							60	0071108	•
							80	0071109	•
							100	0071110	•
							120	0071111	•
19 ±0.8	6.25	31,5 ±0.8	200.0	500	95	0.82	40	5010435	840
							60	0071113	840
							80	0071114	•
							100	0071115	•
							120	0071116	•
25 ±1.0	6.55	38,1 ±1.0	200.0	500	110	1.14	60	0071117	1200
							80	0071118	•
							100	0071119	•
							120	0071120	•
32 ±1.2	6.95	45,9 ±1.2	200.0	500	150	1.57	60	0071121	600
							80	0071122	480
							100	0071123	600
							120	0071124	600

• Upon availability.

\* Tolerance on length: ± 1 % (ISO 1307 Standard)

### Branding



Embossed branding