



TRELLJET 580

TRELLJET 580

BUILDINGS & CONSTRUCTION

Applications

Specially designed for professional and industrial high pressure cleaning. Efficient for machines, vehicles, floors, public areas, facades, etc. The non-staining cover is also an advantage for use in food industry and public baths. Suitable for mobile pressure washers, fixed installations and reel mounted applications.

Advantages

- Non-staining smooth cover.
- Oil, detergent, wear and weather resistant.
- High working pressure.
- High temperature resistance.
- Light weight, flexible and kink resistant.
- Long service life.

Technical description

Inner tube: NBR/SBR, black, smooth.

Reinforcement: steel, two braids.

Cover: SBR/NBR, blue, smooth.

Temperature range: -40 °C to +150 °C.

Couplings/Fittings

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

Complementary information

50% of the volume in each delivery will be random lengths, shortest length of 10m, at least 50% will be in fixed length mentioned in the table.

ID mm	Wall thickness mm	OD mm	Reinf. diameter mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock or min. order m	
7,9	+0.6/-0.2	3.55	15 ±0.7	12.7 ±0.3	650.0	1600	65	0.31	100	2910310	•
9,5	+0.6/-0.2	3.8	17,4 ±0.7	14.9 ±0.3	650.0	1600	70	0.38	100	2910370	•
12,7	+0.8/-0.4	3.75	20,6 ±0.8	18.1 ±0.3	500.0	1200	70	0.47	100	2910420	•

• Upon availability.

* Tolerance on length: ± 1 % (ISO 1307 Standard)

Branding

ND 8mm:



TRELLEBORG



TRELLJET 580 - ND 08 - 5/16" - WP 650 BAR/9560 PSI - MAX 150 °C - 1 Q 13 - Made in France